





MISCELLANEOUS PLUMBING ACCESSORIES

 A black PVC frame with two vertical legs and a horizontal top bar. Each leg has a brass shut-off valve with a blue handle at the bottom.	<p>9050 CORROSION COUPON RACK PART NO. 1167416</p> <p>The 9050 Is A Pvc Four Coupon Holder System. The System Includes An Inlet And Outlet Shutoff Valve, Four (4) Coupon Holders And A 5 Gpm (18.9 Lpm) Flow Regulator.</p> <p>Material Is Pvc Schedule 40 With Brass Regulator And Valves. The Coupon Holder Is ¾ Inch Mnpt, Pvc. The Pressure Rating Is 140 Psi At 100°F (9.7 Bar @ 38°C). The Maximum Temperature Is 140°F (60°C)</p>
 A black PVC component with a threaded top section and a smaller diameter section below.	<p>COUPON HOLDER PART NO. 1167500</p> <p>The Coupon Holder Is ¾ Inch Mnpt, Pvc. The Pressure Rating Is 140 Psi At 100°F (9.7 Bar @ 38°C). The Maximum Temperature Is 140°F (60°C)</p>
 A black PVC assembly with a brass shut-off valve on the right side and a brass sample cock at the bottom.	<p>9102 SAMPLE SHUTOFF ASSEMBLY PART NO. 1167419</p> <p>The 9102 Is A Pvc Inlet Plumbing Assembly With Brass Shut-Off Valve And A Sample- Cock.</p> <p>The Material Is Pvc Schedule 80 With Brass Valves. The Pressure Rating Is 140 Psi At 100°F (9.7 Bar @ 38°C). The Maximum Temperature Is 140°F (60°C). The Connections Are ¾ Inch Npt.</p>

	<p style="text-align: center;">9160 CORPORATION STOP PART NO. 1167423</p> <p>The 9160 Is A Corporation Stop That Will Effectively Disperse Chemicals Such As Acid In The Center Of A Pipe. Process And Chemical Inlet Connections Are 1 Inch Npt. The Quill Diameter Is ½ Inch. The Quill Material Is 316ss. The Quill Adjustment Valve And Process Connections Are Brass. The Chemical Inlet Valve Is Pvc Schedule 80. Also Available In Carpenter 20, Part Number 1167424.</p>
	<p style="text-align: center;">9176 CHEMICAL INJECTION MANIFOLD PART NO. 1167426</p> <p>The 9176 Injection Manifold Is Designed For Use With Four (4) Chemical Injection Points Including Acid. A Sample Valve, Shut Off Valve, And Quick Release Unions Are Included For Easy Removal. The Material Is Pvc, Schedule 40 And 80. There Are Four ½ Fnt, Pvc, Injection Tees, One Is Schedule 80 For Acid. The Maximum Pressure Is 140 Psi @ 100°F (9.7 Bar @ 38°C) The Maximum Temperature Is 140°F (60°C).</p>

MISC PLUMBING ACCESSORIES

PART NO.	DESCRIPTION
1167500	Coupon Holder, PVC ¾" NPT
1167416	9050, PVC corrosion coupon rack
1167419	9102, Controller inlet and shut-off valve with sample cock
1167423	9160, 316 S.S. corporation stop. 1" NPT. CPVC shut off valve
1167426	9176, PVC chemical pump injection manifold for up to 4 chemical pumps